

EVC Accessories



SolaX EVC Pedestal Dual

Feature

- Compatible with SolaX EVC G1 and G2
- Installation accessories included
- Easy to install
- Weather & corrosion resistant

| | |
|-----------|----------------|
| Dimension | 140×60×1400 mm |
| Weight | 6.8 kg |
| Color | Black |



SolaX EVC Rain Shelter

| | |
|------------|----------------|
| Dimension* | 290×406×204 mm |
| Weight* | 1.37kg |
| Color | Black |

*For the assembled Rain Shelter.

SolaX EVC Cable

Feature

- Electric vehicles IEC 62196-2 male-female Type2 EVC connector
- High flame retardant grade
- Long mechanism life withstand over 10000 times matingcycles
- Support for indoor and outdoor charging
- Ergonomic design for easy plug
- Rubber coating for more comfortable touch



| | |
|-----------------------|------------------------|
| Rated Current | 16 / 32 A |
| Rated Voltage | 250 / 480 V |
| Power | 3.7 / 11 / 7.4 / 22 kW |
| No. of Phase | One phase, Three phase |
| Standard | IEC 62196-2 |
| Cable Length | 7.5 m |
| Protection Degree | IP55 |
| Operating temperature | -30~50 C |
| Warranty | 1 year |

SolaX EVC Universal RFID Card

| | |
|-----------|-----------------|
| Dimension | 85.5×54×0.86 mm |
| Material | PVC |
| Standard | ISO-14443-A |



SolaX EVC G2 Front Cover



| | |
|-----------|---------------|
| Dimension | 206×390×21 mm |
| Weight | 355g |
| Color | Black |