

DELTA 3 Ultra Plus Spec

General	Color	Silver
	Capacity	3072Wh
	Net weight	Approx. 33.7kg
	Dimension	613.1 × 327.7 × 395.0 mm
AC Output	AC outlets number	4
	Output priority	YES
	Max AC output	3600W
	Output voltage	230V~50Hz 3600W total, 15.6A(x4) Max per port
	Surge output	7200W
	Max output by X-Boost	4700W
	X-Fusion	YES
DC Output	Number of AC outlets	6
	USB-A	1×18W Max
	USB-C (x1)	5/9/12/15V-3A, 20V/28V~5A, 140W Max (HID supported)
	USB-C (x2)	5/9/12V/15V-3A, 20V-2.25A, 45W Max per port (total 45W)
	12V DC output	Total 378W Max; Car Charging Output1, 12.6V~10A; Anderson Output1, 12.6V~30A
Input	Utility power charging	2300W
	Input voltage	220~240V~10A 50/60Hz
	0~80% charge time	75min (1.3h)
	0~100% charge time	110min (1.8h)
	Solar charging	1600W Max
	Generator charging	2400W Max
	Alternator charging	1000W Max, through 4+8 port
	Car charging	12/24V, 8A

Battery	Battery chemistry	LFP
	Number of extra battery port	1 (expandable to 2)
	Type of extra battery port	4+8
	Extra battery	D3M Plus EB; DP3 EB
	Max capacity with extra battery	Up to 11kWh with 2*DP3 EB
UPS	CTC craftsmanship	CTC
	UPS	10ms+HID, UPS
Connection	Screen	YES
	WIFI	YES
	Bluetooth	YES
	APP	YES
Experience	Years of warranty	3+2 years
	Noise	600W<=25dB
	Discharge temperature	-10 to 45°C
	Charge temperature	0°C~45°C
	Storage temperature	-10°C to 45°C (optimal: 20°C to 30°C)
Battery Protection	Battery protection	Over Voltage Protection, Overload Protection, Over Temperature Protection, Short Circuit Protection, Low Temperature Protection, Low Voltage Protection, Overcurrent Protection
What is in the box	What is in the box?	1. EcoFlow DELTA 3 Ultra Plus Portable Power Station *1; 2. AC Charging Cable *1; 3. Manuals & Warranty Card *1