

MC4-Evo 2 In-line Fuse MC4-Evo 2 Y-Splitter

Renewable Energy | Solar Photovoltaics

EN




DC INTERCONNECTION SOLUTIONS

Best-in-class eBOS components for your PV system


Our DC cabling system offers first-class quality and outstanding functionalities. The unique manufacturing process through vulcanization ensures permanent highest

protection against ingress and will provide best-in-class performance even under harsh climatic conditions.

Worldwide unique vulcanization process



Less material use and short assembly time



Product features and your benefits

Product features and advantages

Customer benefits

Enclosure concept and design (Vulcanization Process)	Best-in-class product reliability <ul style="list-style-type: none"> • Product lifetime expectancy • Insulation performance • Harsh environment compliant 	
Certified product safety	Product trust in safety and reliability <ul style="list-style-type: none"> • Meeting relevant industry standards (2PfG 1911, 2PfG 2380) • Verified by independent third party 	
Track record	Proven long-term reliability <ul style="list-style-type: none"> • Installed base (>4 GW) • Systems operating in harsh environment and conditions 	
Original MC4-Evo 2 connectors	Best-in-class connector technology <ul style="list-style-type: none"> • More reliable and durable operation • Less downtimes and performance losses 	

Solution features and advantages


Customer benefits

Lower total cost of ownership	Cost savings compared to conventional DC cabling design <ul style="list-style-type: none"> • Less material and components used (optimized CAPEX) • Insensitivity due to fewer components and maintenance (optimized OPEX) 	
Plug and play	Time and cost savings compared to field assembly <ul style="list-style-type: none"> • Ready-to-use product design with connector assembly • Reducing potential failure risks due to incorrect installation 	
Stäubli Excellence	Well acknowledged Stäubli quality <ul style="list-style-type: none"> • Trustworthy product and solution source • Controlled supply chain with state-of-the-art quality components 	
Engineered in Europe and sustainable manufactured	Meeting state-of-the-art ESG requirements <ul style="list-style-type: none"> • Highest product quality • Sustainable supply chain and low carbon footprint 	

Y-SPLITTER


MC4-Evo 2 Y-Splitter (PV-K/SPL-Y)

MC4-Evo 2 Y-Splitter



PV-K/SPL-Y...ES... (mit 1 x Buchse and 2 x Stecker)

MC4-Evo 2 Y-Splitter



PV-K/SPL-Y...EP... (mit 2 x Buchse and 1 x Stecker)

Technical data	
Connector system	MC4-Evo 2
Voltage rating	DC 1500 V
Test voltage	8 kV
Safety class	II
Overvoltage category Pollution degree	CATIII/3
Mating connectors, only genuine Stäubli connectors shall be used!	Original MC4 cable coupler and panel receptacle Original MC4-Evo 2 cable coupler and panel receptacle
Ambient temperature range	-40 °C ... +85 °C
Transportation/storage temperature range	-30 °C ... +60 °C
Transportation/storage relative humidity	< 70 %
Degree of Protection (IP), mated unmated	IP65/IP68 (1 m, 1 h) IP2X
Insulation material	PA, EVA, XLPE
Contact material	Copper, tin plated
Max. contact resistance of the connector	< 0.5 mΩ
Certified according to TÜV Rheinland 2PFG 1913	R 60164319

The MC4-Evo 2 Y-Splitter is TÜV Rheinland certified and guarantees a long-lasting, stable connection within a PV DC string: Minimal energy loss, low heat generation. Ro-

bust housing, safety class IP68 (1 m, 1 h). Cable cross-section 6 mm². MC4 and MC4-Evo are registered trademarks owned by Stäubli.

Order No.	Type	TÜV Rheinland (2PFG 1913)		Lead length L (cm)	Connector system	Input Connector	Output Connector	Approvals
		DC V	A					
32.0333	PV-K/SPL-Y-6-15/15-15EPP/ES-0050	1500	53	50	MC4-Evo 2	Plug (2 x)	Socket (1 x)	x
32.0334	PV-K/SPL-Y-6-15/15-15ESS/EP-0050	1500	53	50	MC4-Evo 2	Socket (2 x)	Plug (1 x)	x




Assembly instructions MA706

www.staubli.com/electrical

IN-LINE FUSE

MC4-Evo 2 In-line Fuse (PV-K/ILF3)

MC4-Evo 2 In-line Fuse



PV-K/ILF3...

Technical data	
Connector system	MC4-Evo 2
Voltage rating	DC 1500 V
Test voltage	8 kV
Safety class	II
Overvoltage category Pollution degree	CATIII/3
Mating connectors, only genuine Stäubli connectors shall be used!	Original MC4 cable coupler and panel receptacle Original MC4-Evo 2 cable coupler and panel receptacle
Rated current gPV	4 A 15 A 5 A 20 A 6 A 25 A 10 A 30 A
Ambient temperature range	-40 °C ... +50 °C
Transportation/storage temperature range	-40 °C ... +50 °C
Transportation/storage relative humidity	< 70 %
Degree of Protection (IP), mated unmated	IP65/IP68 (1 m, 1 h) IP2X
Insulation material	PA, EVA, XLPE
Contact material	Copper, tin plated
Max. contact resistance of the connector	< 0.25 mΩ
Certified according to TÜV Rheinland 2PFG 2380	R 60163375

The MC4-Evo 2 In-line Fuse (PV-K/ILF3) with a crimping connection guarantees a long-lasting, stable connection in comparison to conventional omega-style clips: Minimal energy loss, low heat generation. Ro-

bust housing, safety class IP68 (1 m, 1 h). Cable cross-section 6 mm². MC4 and MC4-Evo are registered trademarks owned by Stäubli.

Order No.	Type	TÜV Rheinland (2PFG 2380)		Lead length L (cm)	Connector system	Approvals TÜV
		DC V	A			
32.0326	PV-K/1500ILF3-4/6E-0059	1500	4	59	MC4-Evo 2	x
32.0327	PV-K/1500ILF3-5/6E-0059	1500	5	59	MC4-Evo 2	x
32.0328	PV-K/1500ILF3-6/6E-0059	1500	6	59	MC4-Evo 2	x
32.0399	PV-K/1500ILF3-10/6E-0059	1500	10	59	MC4-Evo 2	x
32.0329	PV-K/1500ILF3-15/6E-0059	1500	15	59	MC4-Evo 2	x
32.0330	PV-K/1500ILF3-20/6E-0059	1500	20	59	MC4-Evo 2	x
32.0331	PV-K/1500ILF3-25/6E-0059	1500	25	59	MC4-Evo 2	x
32.0332	PV-K/1500ILF3-30/6E-0059	1500	30	59	MC4-Evo 2	x





Assembly instructions MA707

www.staubli.com/electrical

Y-SPLITTER + IN-LINE FUSE



MC4-Evo 2 Y-Splitter and In-line Fuse (PV-K/SPL-Y/ILF3)

MC4-Evo 2 Y-Splitter and In-line Fuse



PV-K/SPL-Y/ILF3...-PPS

MC4-Evo 2 Y-Splitter and In-line Fuse



PV-K/SPL-Y/ILF3...-SSP

Technical data	
Connector system	MC4-Evo 2
Voltage rating	DC 1500 V
Test voltage	8 kV
Safety class	II
Overvoltage category Pollution degree	CATIII/3
Mating connectors, only genuine Stäubli connectors shall be used!	Original MC4 cable coupler and panel receptacle Original MC4-Evo 2 cable coupler and panel receptacle
Rated current gPV	4 A 15 A 5 A 20 A 6 A 25 A 10 A 30 A
Ambient temperature range	-40 °C ... +50 °C
Transportation/storage temperature range	-40 °C ... +50 °C
Transportation/storage relative humidity	< 70 %
Degree of Protection (IP), mated unmated	IP65/IP68 (1 m, 1 h) IP2X
Insulation material	PA, EVA, XLPE
Contact material	Copper, tin plated
Max. contact resistance of the connector	< 0.25 mΩ
Certified according to TÜV Rheinland 2PFG 1913 and 2PFG 2380	Statement available

The MC4-Evo 2 Y-Splitter and In-line Fuse combination product aggregates the unique advantages within one product.

The crimping connections guarantee a long-lasting, stable connection with minimal

energy loss and low heat generation. Robust housing, safety class IP68 (1 m, 1 h).

Cable cross-section 6 mm².

MC4 and MC4-Evo are registered trademarks owned by Stäubli.

Order No.	Type	TÜV Rheinland (2PFG 2380 and 2PFG 1913)		Lead length L (cm)	Connector system	Input Connector	Output Connector	Approvals TÜV
		DC V	A					
32.0373	PV-K-SPL-Y/2-ILF3-4/6/E-PPS	1500	4	84	MC4-Evo 2	Socket (1 x)	Plug (2 x)	x
32.0374	PV-K-SPL-Y/2-ILF3-4/6/E-SSP	1500	4	84	MC4-Evo 2	Plug (1 x)	Socket (2 x)	x
32.0375	PV-K-SPL-Y/2-ILF3-5/6/E-PPS	1500	5	84	MC4-Evo 2	Socket (1 x)	Plug (2 x)	x
32.0376	PV-K-SPL-Y/2-ILF3-5/6/E-SSP	1500	5	84	MC4-Evo 2	Plug (1 x)	Socket (2 x)	x
32.0377	PV-K-SPL-Y/2-ILF3-6/6/E-PPS	1500	6	84	MC4-Evo 2	Socket (1 x)	Plug (2 x)	x
32.0378	PV-K-SPL-Y/2-ILF3-6/6/E-SSP	1500	6	84	MC4-Evo 2	Plug (1 x)	Socket (2 x)	x
32.0379	PV-K-SPL-Y/2-ILF3-10/6/E-PPS	1500	10	84	MC4-Evo 2	Socket (1 x)	Plug (2 x)	x
32.0380	PV-K-SPL-Y/2-ILF3-10/6/E-SSP	1500	10	84	MC4-Evo 2	Plug (1 x)	Socket (2 x)	x
32.0381	PV-K-SPL-Y/2-ILF3-15/6/E-PPS	1500	15	84	MC4-Evo 2	Socket (1 x)	Plug (2 x)	x
32.0382	PV-K-SPL-Y/2-ILF3-15/6/E-SSP	1500	15	84	MC4-Evo 2	Plug (1 x)	Socket (2 x)	x
32.0383	PV-K-SPL-Y/2-ILF3-20/6/E-PPS	1500	20	84	MC4-Evo 2	Socket (1 x)	Plug (2 x)	x
32.0384	PV-K-SPL-Y/2-ILF3-20/6/E-SSP	1500	20	84	MC4-Evo 2	Plug (1 x)	Socket (2 x)	x
32.0391	PV-K-SPL-Y/2-ILF3-25/6/E-PPS	1500	25	84	MC4-Evo 2	Socket (1 x)	Plug (2 x)	x
32.0392	PV-K-SPL-Y/2-ILF3-25/6/E-SSP	1500	25	84	MC4-Evo 2	Plug (1 x)	Socket (2 x)	x
32.0393	PV-K-SPL-Y/2-ILF3-30/6/E-PPS	1500	30	84	MC4-Evo 2	Socket (1 x)	Plug (2 x)	x
32.0394	PV-K-SPL-Y/2-ILF3-30/6/E-SSP	1500	30	84	MC4-Evo 2	Plug (1 x)	Socket (2 x)	x



Assembly instructions MA715

www.staubli.com/electrical

Standard cable assemblies

MC4 cable assembly



PV-K4..../PV-KBT4/6X/1PV-KST4/6X/...

MC4-Evo 2 cable assembly



PV-K4..../PV-EVO2-BI/PV-EVO2-BI/...

These extensions help to connect your PV components to the PV system. IEC 62930 certified PV DC pre-assembled cable.

Please review specifications for your installation.

MC4 and MC4-Evo are registered trademarks owned by Stäubli.

Technical data

Connector system	Stäubli MC4 and MC4-Evo 2 product family
Voltage rating IEC 62852:2014+Amd 2:2020 2 PfG 2330/03.23 UL6703	MC4: DC 1000 V / MC4-Evo 2: DC 1500 V MC4: DC 1500 V ¹⁾ MC4: DC 1500 V
Ambient temperature range	-40 °C...+85 °C (IEC) -40 °C...+85 °C (UL)
Transportation/storage temperature range	-30 °C/+60 °C
Transportation/storage relative humidity	< 70 %
Safety instruction	Do not disconnect under load

Mating connectors:
Only Original Stäubli connectors shall be used!

¹⁾ IEC DC 1500 V: Only for use in PV-systems in access-restricted areas.

Attention

When connecting the connectors, it must be ensured that the rated data (current carrying capacity and rated voltage) of the products are dependent on the mating connectors used. Observe the information in the assembly instructions for the connectors used.

Order No.	Length	Cable cross-section	Connector system
13002820-100	1 m	4 mm ²	MC4
13002820-150	1.5 m		
13002820-200	2 m		
13002820-300	3 m		
13002820-500	5 m		
13002820-10M	10 m		
13002812-100	1 m	6 mm ²	MC4
13002812-150	1.5 m		
13002812-200	2 m		
13002812-300	3 m		
13002812-500	5 m		
13002812-10M	10 m		
13002843-100	1 m	4 mm ²	MC4-Evo 2
13002843-150	1.5 m		
13002843-200	2 m		
13002843-300	3 m		
13002843-500	5 m		
13002843-10M	10 m		
13002844-100	1 m	6 mm ²	MC4-Evo 2
13002844-150	1.5 m		
13002844-200	2 m		
13002844-300	3 m		
13002844-500	5 m		
13002844-10M	10 m		




Assembly instructions MA711

www.staubli.com/electrical


Customer and application specific cable assemblies

MC4-Evo 2 In-line Fuse (PV-K/ILF3) according to your request




Please send your request to:
eBOS.solutions@staubli.com

MC4-Evo 2 Y-Splitter (SPL-Y) according to your request
























Please send your request to:
eBOS.solutions@staubli.com

MC4-Evo 2 Y-Splitter + In-line Fuse (PV-K/SPL-Y/ILF3) according to your request



Cable extensions according to your request

<p>Side 1</p> <p>MC4 cable coupler</p> <p><input type="checkbox"/> PV-KBT4 </p> <p><input type="checkbox"/> PV-KST4 </p> <p>MC4-Evo 2 cable coupler</p> <p><input type="checkbox"/> PV-KBT4-EVO 2 </p> <p><input type="checkbox"/> PV-KST4-EVO 2 </p> <p>MC4 panel receptacle</p> <p><input type="checkbox"/> PV-ADBP4-S2 </p> <p><input type="checkbox"/> PV-ADSP4-S2 </p> <p>MC4-Evo 2 panel receptacle</p> <p><input type="checkbox"/> PV-ADB4-EVO 2 </p> <p><input type="checkbox"/> PV-ADS4-EVO 2 </p> <p>MC4-Evo stor</p> <p><input type="checkbox"/> PV-KBT4-EVO ST </p> <p><input type="checkbox"/> PV-KST4-EVO ST </p>	<p>Cable</p> <p>Cable cross section (mm²):</p> <p><input type="checkbox"/> 4 mm <input type="checkbox"/> 6 mm</p> <p>Length of cable extension: (Cable certified according IEC62930)</p> <p><input type="text" value=""/> cm</p>	<p>Side 2</p> <p>MC4 cable coupler</p> <p> PV-KBT4 <input type="checkbox"/></p> <p> PV-KST4 <input type="checkbox"/></p> <p>MC4-Evo 2 cable coupler</p> <p> PV-KBT4-EVO 2 <input type="checkbox"/></p> <p> PV-KST4-EVO 2 <input type="checkbox"/></p> <p>Cable lug</p> <p> Ø <input type="text" value=""/></p> <p> Ø <input type="text" value=""/></p> <p>End sleeve for strands</p> <p> Ø <input type="text" value=""/></p> <p> Ø <input type="text" value=""/></p> <p>Partial stripping <input type="checkbox"/></p> <p> Length <input type="text" value=""/> (max. 45 mm)</p> <p>Not stripped <input type="checkbox"/></p> <p></p>
---	--	--



Please send your request to:
eBOS.solutions@staubli.com



● Stäubli Units ○ Representatives/Agents

Global presence of the Stäubli Group

www.staubli.com