

## Connectors, straight for cables Ø 6 – 10 mm and 10 – 14 mm

### Female connector

Unmounted with cable gland.

Crimp contacts separately available under Accessories.

See the Technical Data for sheath and insulation strip lengths.



#### with screw connection<sup>1)</sup>

Wire	mm <sup>2</sup>
rigid	
fine-stranded	0.75 – 4.0
stranded	without ferrules

#### with crimp connection

Wire	mm <sup>2</sup>
fine-stranded	0.75 – 4.0

Application	Coding	Cable diameter in mm	Color
250/400V	⊕, N, 3, 2, 1	6 – 10	light gray
		10 – 14	black
	L, ⊕, N, D1, D2	6 – 10	light gray
		10 – 14	black
	1, 2, 3, 4, 5	6 – 10	turquoise
		10 – 14	turquoise
-50/-120V	1, 2, 3, 4, 5	6 – 10	light blue
		10 – 14	light blue
	N, E, 1, 2, 3	6 – 10	yellow
		10 – 14	yellow
1, 2, 3, 4, 5	6 – 10	signal	
	10 – 14	brown	

Part No.
96.051.4053.0
96.051.4053.1
96.051.4153.0
96.051.4153.1
96.051.4053.6
96.051.4153.6
96.051.4053.9
96.051.4153.9
96.051.4053.2
96.051.4051.4
96.051.4151.4

Part No.
96.151.0053.0
96.151.0053.1
96.151.0153.0
96.151.0153.1
96.151.0053.6
96.151.0153.6
96.151.0053.9
96.151.0153.9
96.151.0051.4
96.151.0151.4

Contacts separately under Accessories, see following pages.

### Male connector

Unmounted with cable gland and locking device.

Crimp contacts separately available under Accessories.

See the Technical Data for sheath and insulation strip lengths.



#### with screw connection<sup>1)</sup>

Wire	mm <sup>2</sup>
rigid	
fine-stranded	0.75 – 4.0
stranded	without ferrules
Locking device	yes

#### with crimp connection

Wire	mm <sup>2</sup>
fine-stranded	0.75 – 4.0
Locking device	yes

Application	Coding	Cable diameter in mm	Color
250/400V	⊕, N, 3, 2, 1	6 – 10	light gray
		10 – 14	black
	L, ⊕, N, D1, D2	6 – 10	light gray
		10 – 14	black
	1, 2, 3, 4, 5	6 – 10	turquoise
		10 – 14	turquoise
-50/-120V	1, 2, 3, 4, 5	6 – 10	light blue
		10 – 14	light blue
	N, E, 1, 2, 3	6 – 10	yellow
		10 – 14	yellow
1, 2, 3, 4, 5	6 – 10	signal	
	10 – 14	brown	

Part No.
96.052.4053.0
96.052.4053.1
96.052.4153.0
96.052.4153.1
96.052.4053.6
96.052.4153.6
96.052.4053.9
96.052.4153.9
96.052.4053.2
96.052.4051.4
96.052.4151.4

Part No.
96.152.0053.0
96.152.0053.1
96.152.0153.0
96.152.0153.1
96.152.0053.6
96.152.0153.6
96.152.0053.9
96.152.0153.9
96.152.0051.4
96.152.0151.4

Contacts separately under Accessories, see following pages.

<sup>1)</sup> With wire protection available on request